



Milwaukee MI-CD601 Digital Conductivity Pen (EC)



SPECIFICATIONS

- Range:** 0 to 1990 $\mu\text{S}/\text{cm}$
- Resolution:** 10 $\mu\text{S}/\text{cm}$
- Accuracy:** $\pm 2\%$ Full Scale
- Typical EMC Deviation:** $\pm 1\%$ Full Scale
- Calibration:** Manual, at 1 point through trimmer
- Temperature Compensation:** Automatic from 5 to 50°C (41 to 122°F), with $\beta=2\%/^{\circ}\text{C}$
- Environment:** 0 to 50°C / 32 to 122°F; max RH 100%
- Calibration Solution:** M10031B (25 sachets x 20 mL ea.)
- Battery Type:** 4 x 1.5V Alkaline (included)
- Battery Life:** Approx. 350 hours of continuous use

DESCRIPTION

•DIGITAL. SIMPLE. COMPACT.

The Milwaukee MI-CD601 digital electrical conductivity (EC) Pen is designed for aquariums, aquaculture, pools, water conditioning and many other applications. The MI-CD601 helps you make sure that your water has the right amount of nutrient to help keep fish tanks healthy or helps you keep your filters up-to-date and clean for water filtration. Keep EC in your target range to help you achieve better results.



DESIGN FEATURES

- Measures microSiemens ($\mu\text{S}/\text{cm}$) direct and with automatic temperature compensation.
- Ideal range for aquariums (0 to 1990 $\mu\text{S}/\text{cm}$).
- Units in $\mu\text{S}/\text{cm}$ are easily convertible to (ppm).
- Factory calibrated with the ability to recalibrate if needed.
- Automatic Temperature Compensation (ATC).
- 350 hours continuous use (4 x 1.5V batteries included).
- Simple one point calibration.



CONVERTING EC TO TDS

The Milwaukee EC Pen, like all conductivity meters, provides a measure of electrically charged ions in a solution and is an absolute measure of conductivity.

EC is often converted to TDS in parts per million (ppm). Different scales include the 500 scale, 650 scale and the 700 scale. However, true PPM can only be determined through chemical analysis.

Your mS/cm reading can be approximately converted to TDS (ppm) as shown in the examples below.

$2,000 \mu\text{S}/\text{cm} = 2.0 \text{ mS}/\text{cm} = 1000 \text{ ppm}$ on .50 factor scale

$2,000 \mu\text{S}/\text{cm} = 2.0 \text{ mS}/\text{cm} = 1400 \text{ ppm}$ on the 442 scale or .70 factor scale.

Thank you for considering Milwaukee to help you take your results to the next level.



CARE AND USE

MAINTENANCE

EC electrodes can develop nutrient build up over time. To minimize build up, always rinse the probe in fresh tap water after every use.